

MP-100

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

The iNetVu® MP-100 is a robust, lightweight, 100 cm multi-segment carbon fiber manpack antenna system which can be setup and pointed to the target satellite manually within minutes.



Soft Case Solution (Standard)

SatAssist 1000

Features

- 100 cm 7-piece carbon fibre reflector
- Single Backpack Case Solution
- Operates in Ku, Ka or X band
- Azimuth & Elevation angle adjustment with fast and fine tuning operations using the handheld iNetVu® SatAssist 1000 pointing tool
- Motorized two-axis Azimuth/Elevation Optional
- Captive hardware / fasteners
- No tools required for assembly / disassembly
- Set-up time less than 10 minutes, one person job
- 1 Year Standard Warranty

Application Versatility

The MP-100 Manual Flyaway system can be easily configured to provide quick access to satellite communications for any application that requires remote connectivity in a rugged environment. Ideally suited for applications that require a quick, simple set-up; in vertical markets such as emergency response, disaster management, public safety, broadcast, media and more.

C-COM
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)
www.c-comsat.com

Specifications are subject to change

Draft Nov 2018

MP-100

iNetVu®

by C-COM Satellite Systems Inc.

TECHNICAL SPECIFICATIONS

Mechanical

Reflector	100 cm segmented carbon fibre
Number of Petals	7
Platform Geometry	Elevation over Azimuth
Antenna Optics	Centre Feed
Azimuth	$\pm 180^\circ$
Elevation	$10^\circ - 90^\circ$
Polarization	$\pm 95^\circ$

Environmental

Wind loading	
Operational	
Without Ballast / Anchors	25 km/h (15 mph)
With Ballast/Anchors	72 km/h (45 mph)
Temperature	
Operational	-40° to 60° C (-40° to 140° F)

Case

Single Backpack Soft Case (Empty): 6.6 Kg (14.5 lbs)
Size: 84 x 51 x 41 cm (33.0" x 20.0" x 16.0")
Weight (Incl. Ku Antenna⁽¹⁾): 20 Kg (44 lbs)
Optional: Hard Case TBD
Rugged Case Size: TBD

Shipping Weights & Dimensions*

TBD

*The shipping weights/dims can vary for particular shipments depending on actual system configuration, quantity, packaging materials and special requirements



Ku-Band (Linear)

Transmit Power	1 to 200 watt	
Feed	2 Port XPol	
	Receive	Transmit
Frequency (GHz)	10.70- 12.75	13.75 - 14.50
Feed Interface	WR75	WR75
Midband Gain ($\pm .2$ dBi)	40.10	41.40
Sidelobe Envelope Co-Pol (dBi)		
100 λ /D $^\circ$ < Θ < 7 $^\circ$	35-25 Log Θ	
7 $^\circ$ < Θ < 9.2 $^\circ$	13.9	
9.2 $^\circ$ < Θ < 48 $^\circ$	38-25 Log Θ	
48 $^\circ$ < Θ < 180 $^\circ$	-4 Typical	
Cross-Polarization on Axis	>35 dB	
Within 1dB Beamwidth	>30 dB	
Tx/Rx Isolation	40 dB	85 dB
VSWR	1.3:1	1.3:1

Ka-Band (Circular)

	Receive	Transmit
Operating Frequency (GHz)	19.20 - 21.20	29.0 - 31.0
Midband Gain ($\pm .2$ dBi)	44.50	47.60
Polarization X-POL	LHCP/RHCP	
Feed Interface	WR-42	WR-28
VSWR	<1.5:1	<1.25:1
Isolation (dB)	>55	>55

X-Band (Circular)

	Receive	Transmit
Operating Frequency (GHz)	7.25 - 7.75	7.90 - 8.40
Midband Gain ($\pm .5$ dB)	36.40	37.0
Polarization X-POL	LHCP/RHCP	
Sidelobe Compliant with	DSCS Req.	
Feed Interface	WR-112	WR-112
VSWR	<1.25:1	<1.25:1
Isolation (dB)	>23	>23

Notes:

⁽¹⁾ Weight indicated does not include BUC, LNB and Cables

C-COM
SATELLITE SYSTEMS INC.

613-745-4110 | 1-877-463-8886 (1-877-iNetVu6)
www.c-comsat.com

Specifications are subject to change

Draft

Nov 2018